

**Parameters lift and slide door P-Line HST 13.2/2022/ glass 4/18TGI/4/18TGI/4**

1. Door: **13.2 – HST Scheme C,**
2. Intended use: Exterior doors intended for installation in residential, public and commercial buildings
3. Producer: DOBROPLAST Fabryka Okien Sp. z o.o., Stary Laskowiec 4, 18-300 Zambrów.
4. Harmonised standard: EN 14351-1:2006+A2:2016.

Characteristic	Parameters
Wind resistance	Class C2
Waterproofness	Class 9A
Air permeability	Class 4
Sound reduction	max Rw = 26(-1;-3)dB
Thermal transmittance: scheme C, 5000 x 2600 mm, glass 4/18TGI/4/18TGI/4, Ug=0,5 W/m <sup>2</sup> K, (calculatingly, EN ISO 10077-1)	Ud = 0,79 W/m <sup>2</sup> K

Signed on behalf of producer by:  
Artur Kruszewski, R&D

Stary Laskowiec, 31.05.2022r.

**DOBROPLAST**  
FABRYKA OKIEN sp. z o.o.  
STARY LASKOWIEC 4, 18-300 Zambrów  
KRS 0000404303 Regon 145908247  
NIP 5252523303  
tel. +48 86 276 35 50, fax +48 85 674 32 55



**Artur Kruszewski**  
KIEROWNIK DZIAŁU CERTYFIKACJI