

## Parameters lift and slide door P-Line HST13.2/2025/ glass 4/18/4/18/4

1. Type: **13.2 – HST Schema C,**
2. Intended use: Exterior doors intended for installation in residential, public and commercial buildings
3. Producer: DOBROPLAST Fabryka Okien Sp. z o.o., Stary Laskowiec 4, 18-300 Zambrów, Poland
4. Harmonised standard: EN 14351-1:2006+A2:2016.

Characteristic	Parameters
Wind resistance	Class C2
Waterproofness	Class 9A
Air permeability	Class 4
Sound reduction	Max Rw= 26(-1;-3)dB
Thermal transmittance; scheme C 5000x2600mm, <b>vetro 4/18AST/4/18AST/4, Ug=0,5 W/m²K,</b> (calculatingly, EN ISO 10077-1)	Ud=0,80W/m²K
Thermal transmittance; scheme C 5000x2600mm, <b>vetro 4/18TGI/4/18TGI/4, Ug=0,5 W/m²K,</b> (calculatingly, EN ISO 10077-1)	Ud=0,77 W/m²K

Signed on behalf of the producer by:  
Tomasz Barczak, R&D

Stary Laskowiec, 13.01.2025.



**Tomasz Barczak**  
Dział Certyfikacji

